



# AcroPack® Modules

## AP500 Serial RS232 Communication



### Four RS232 Serial Ports ♦ Extended Temperature ♦ PCIe Bus Interface

#### Description

The AcroPack® product line updates our popular Industry Pack I/O modules with a PCIe interface format. This tech-refresh design offers a compact size, low-cost I/O, the same functionality and memory map of the existing Industry Pack modules and a rugged form factor.

The AP500 modules provide four asynchronous serial communication interfaces for your system. Software-configuration helps you quickly set baud rates, character-sizes, stop bits, and parity. Full signal support for modem control is also included.

For more efficient data processing, each serial port is equipped with 256-character FIFO buffers on the transmit and receive lines.

The data ports generate individually controlled transmit, receive, line status, and data set interrupts. All interrupts can be read from a single register.

The AP500 series modules are 70mm long, this is 19.05mm longer than the full-length mini-PCIe card at 50.95mm. The board's width is the same as mPCIe board of 30mm and they use the same mPCIe standard board hold down standoff and screw keep out areas.

A down facing 100 pin Samtec connector will mate with the carrier card. Fifty of these signals are available as field I/O signals. Pin spacing and signal assignments will allow for 100V of signal to signal isolation.

The AP500 series maintains the same functionality and memory map of the existing Industry Pack modules providing a smooth transition to the AcroPack I/O modules.

#### Key Features & Benefits

- PCI Express Generation 1 interface
- Four RS232E serial ports
- 256-byte FIFO buffers
- Programmable baud rate (up to 500Kbps)
- Individual modem control signals on each channel
- Handshake lines (RTS, CTS, DTR, DSR, DCD, RI)
- Line-break and false start-bit detection
- 16550 compatible register set
- 256-byte FIFO buffers minimize CPU interaction for improved system performance.
- Each serial channel provides full handshake support to simplify interfacing with modems.
- Extended temperature range



# AcroPack® Modules

## AP500 Serial RS232 Communication

### Performance Specifications

#### ■ RS232E Serial Ports

##### Configuration

Independent, non-isolated serial ports with a common single return connection and configured as a DTE device.

##### Data Rate

Programmable up to 500K bits/second using internal baud rate generator.

##### Max. Cable Length

15 meters (50 feet) typical, limited to a cable capacitive load of 2500pF

##### Character size

5 to 8 bits, software-programmable

##### Parity

Odd, even, or no parity; software-programmable.

##### Stop bits

1, 1-1/2, or 2 bits; software-programmable

##### Data register buffers

256-byte receive FIFO buffer and 256-byte transmit FIFO buffer.

##### Interrupts

Receiver line status (overrun, parity, framing error, or break interrupt); received data available (FIFO level reached) or character time-out; transmitter holding register empty ; or modem status (CTS, DSR, RI, or DCD).

#### ■ PCI Express Base Specification

Conforms to revision 2.0

##### Lanes

1 lane in each direction

##### Bus Speed

2.5 Gbps (Generation 1)

##### Memory

8k space required

1 base address register

#### ■ Environmental

##### Operating temperature

-40 to 70°C

-40 to 85°C

(requires an AcroPack heatsink conduction-cool kit)

##### Storage temperature

-55 to 125°C

##### Relative humidity

5 to 95% non-condensing

##### Power

+3.3V (±5%) 100mA typical

#### ■ Physical

##### Length

70mm

##### Width

30mm

### Ordering Information

#### AcroPack® Modules

##### [AP500E-LF](#)

Four RS232E serial ports

(Note: AcroPack modules are compatible only with the carriers listed below)

#### Accessories

##### [AP-CC-01](#)

Conduction-cool kit

#### Carrier Cards

##### [APCe7010E-LF](#)

PCIe AcroPack carrier, holds one AcroPack module, air-cooled.

##### [APCe7020E-LF](#)

PCIe AcroPack carrier, holds two AcroPack modules, air-cooled.

##### [APCe7040E-LF](#)

PCIe AcroPack carrier, holds four AcroPack modules, air-cooled.

##### [VPX4500E-LF](#)

3U VPX AcroPack carrier, holds three AcroPack modules, air-cooled.

##### [VPX4500-CC-LF](#)

3U VPX AcroPack carrier, holds three AcroPack modules, conduction-cooled.

##### [XMCAP2020-LF](#)

XMC AcroPack carrier; holds two AcroPack modules, 2-slots out front, air-cooled.

##### [XMCAP2021-LF](#)

XMC AcroPack carrier; holds two AcroPack modules, 2-slots out rear, air-cooled.

#### Software (see software documentation for details)

##### [APSW-API-VXW](#)

VxWorks® software support package.

##### [APSW-API-WIN](#)

Windows® DLL driver software support package.

##### [APSW-API-LNX](#)

Linux® support (website download only).



AP-CC-01 Conduction-Cool Kit

