
ATX WITH FRONT ADAPTORS

ATX with front connections for 482.6 mm (19") installation, 4 U





Technical specifications

482.6 mm (19") rack-mount system for the installation of ATX/Mini-ATX or Micro-ATX boards and 1 x 51/4" and 1 x 31/2" drives.

Width: 482.6 mm (19")

Height: 4 U Flanges: 177.0 mm Side panels: 174.0 mm Total depth: 442.5 mm Connections for I/Os, front EMC prepared. Suitable for

mounting on slide rails

Material/surface finish

Case, covers: 1.2 mm sheet steel, spray-finished in RAL 7035, unpainted contact point

Supply includes

- 1 Rack-mount system 4 U including drive holder
- 19" flanges
- 2 x 120 mm fans
- ATX power pack 350 W
- 5 LED displays
- Reset button 6
- 7 On/off switch

- Cover
- 9 Rear panel with cutout and connection for power pack
- 10 Mounting bar for card retainer
- Drive holder for 1 x 51/4" and 1 x 31/2"
- Drive holder for 3 x 31/2" and hard drives

Standards

Complies with IEC 60 297-3 and ATX specification 2.01

	Packs of		Page
U		4	
Width mm		482.6 (19")	
Height of flanges/side panels mm		177.0/174.0	
Depth mm		442.5/440.0	
Model No. basic system fully assembled	1	3659.700	
Accessories			
Card retainer	7	3659.010	215
Unused slot cover	5	3659.030	214
Cover for 51/4" drive space	1	3659.110	214
Cover for 3½" drive space	1	3659.410	214
Telescopic slides for 600 mm enclosure depth	1 set	3659.180	214
Telescopic slides for 800 mm enclosure depth	1 set	3659.190	214
13 Front handles for ATX 4 U	2	3659.240	215

Other customised subrack solutions are available upon request. Please get in contact with one of our sales representatives for further assistance: Tel. +49 9126 - 29 34 0