IP-215P005/030S

Full IP65 PCAP Touch Panel PC



Feature

- ✓ Fanless design and compact solution
- ✓ Intel® Bay Trail Quad Core J1900 2.0GHz CPU
- ✓ Resolution 1920 x 1080 dpi
- ✓ PCAP touch solution
- ✓ Full IP65 Silver Stainless chassis
- ✓ All IP65 stainless connector
- √ 3 x USB, 2 x RS232, 1 x GLAN
- ✓ VESA mounting

System CPU Intel® Bay Trail D-J1900 2.0GHz Quad Core Processor (On Board) Memory 1 x 204-pin DDR3L SODIMM up to 8 GB H/W Monitor Watchdog Timer 256-Level Watchdog Timer I/O Ports RS232 2 GLAN 1 USB 3 Storage Storage 1 x SATA 2.0 2.5" HDD/SSD Expansion Mini-PCle 1 x Full-size (one w/ mSATA) Power Requirement			
Core Processor (On Board) I x 204-pin DDR3L SODIMM up to 8 GB H/W Monitor Watchdog Timer 256-Level Watchdog Timer I/O Ports RS232 2 2 GLAN 1 USB 3 Storage Storage 1 x SATA 2.0 2.5" HDD/SSD Expansion Mini-PCle 1 x Full-size (one w/ mSATA)	System		
H/W Monitor Watchdog Timer 256-Level Watchdog Timer I/O Ports RS232 2 2 GLAN 1 USB 3 Storage Storage 1 x SATA 2.0 2.5" HDD/SSD Expansion Mini-PCle 1 x Full-size (one w/ mSATA)	СРИ	·	
Watchdog Timer I/O Ports RS232 GLAN USB Storage Storage 1 x SATA 2.0 2.5" HDD/SSD Expansion Mini-PCle 1 x Full-size (one w/ mSATA)	Memory		
I/O Ports RS232 2 GLAN 1 USB 3 Storage 1 x SATA 2.0 2.5" HDD/SSD Expansion Mini-PCle 1 x Full-size (one w/ mSATA)	H/W Monitor		
RS232 2 GLAN 1 USB 3 Storage 1 x SATA 2.0 2.5" HDD/SSD Expansion 1 x Full-size (one w/ mSATA)	Watchdog Timer	256-Level Watchdog Timer	
GLAN 1 USB 3 Storage 1 x SATA 2.0 2.5" HDD/SSD Expansion 1 x Full-size (one w/ mSATA)	I/O Ports		
USB 3 Storage Storage 1 x SATA 2.0 2.5" HDD/SSD Expansion Mini-PCle 1 x Full-size (one w/ mSATA)	RS232	2	
Storage Storage 1 x SATA 2.0 2.5" HDD/SSD Expansion Mini-PCle 1 x Full-size (one w/ mSATA)	GLAN	1	
Storage 1 x SATA 2.0 2.5" HDD/SSD Expansion Mini-PCle 1 x Full-size (one w/ mSATA)	USB	3	
Expansion Mini-PCle 1 x Full-size (one w/ mSATA)	Storage		
Mini-PCle 1 x Full-size (one w/ mSATA)	Storage	1 x SATA 2.0 2.5" HDD/SSD	
,	Expansion		
Power Requirement	Mini-PCIe	1 x Full-size (one w/ mSATA)	
	Power Requirement		
Power Input Voltage DC in 12V for 005S; 24Vfor 030S	Power Input Voltage	DC in 12V for 005S; 24Vfor 030S	
Touch Screen			
Touch screen PCT	Touch screen	PCT	
OS support			
Win Pro , 7,8,10, Embedded Win 7,8,10			

Display	
Size	21.5" TFT (16:9)
Resolution	1920 x 1080
Colors	16.7 M
Luminance (cd/m2)	300
Contrast Ratio	3000:1
View Angle (H / V)	178/178

17 0/ 17 0		
Mechanical & Environmental		
0 ~ 45°C		
10 ~ 90%, non-condensing		
VESA mounting(100X100mm)		
607 x 401 x67.1 (13kg)		
1		
1		
1		
1		
1		
1		

Optional High Brightness Panel	
Resolution	1920 x 1080
Color	16.7 M
Luminance(cd/m2)	1600
Contrast Ratio	900:1
Viewing Angle (H/V°)	178/178

^{*}Specifications are subject to change without notice.

