

SE-121RS

Open Frame 5 wire Resistive Touch Monitor



Feature

- ✓ Fanless design and compact solution
- ✓ Resolution 800 x 600 & 1024 x 768 dpi
- ✓ 5 wires resistive touch solution
- ✓ Rich I/O ports for choice
- ✓ VESA mounting & Open Frame

| I/O Port | | | |
|----------------------------|-------------------------------------|---|-----------------|
| SE121RS03 | SE121RS04 | SE121RS05 | SE121RS06 |
| VGA | VGA | VGA | DP |
| DVI | HDMI | HDMI | DVI |
| / | DP | DVI | / |
| USB or RS232 | USB or RS232 | USB or RS232 | USB or RS232 |
| Power | | | |
| DC IN 12 V | | | |
| Touch Screen | | OS Support | |
| 5 wire resistive | | Win 7,8,10; Win Embedded 7,8,10, Win pro 7,8,10 | |
| Display | | | |
| Size | 12.1" TFT (4:3) | | 12.1" TFT (4:3) |
| Resolution | 800 x 600 | | 1024 x 768 |
| Colors | 16.2M | | 16.2M |
| Luminance (cd/m2) | 450 | | 500 |
| Contrast Ratio | 700:1 | | 700:1 |
| View Angle (H / V) | 160/150 | | 160/160 |
| Mechanical & Environmental | | | |
| Operation Temperature | 0 ~ 45 °C | | |
| Storage Temperature | -10°C ~ 70°C | | |
| Storage Humidity | 10 ~ 90%, non-condensing | | |
| Mount | VESA mounting(75X75mm) & Open Frame | | |
| Optional | | | |
| No Touch Screen | 1 | | |
| AR Glass | 1 | | |

*Specifications are subject to change without notice.